


Technical drawing of a rectangular frame. The overall width is 100, divided into three sections: 50, 100, and 50. The overall height is 85, divided into three sections: 10, 10, and 65. The inner opening is 98 wide and 65 high. The drawing includes two detail callouts: DETAIL 4 on the left and DETAIL 5 on the right. A small component is shown in the center of the top edge, marked with an 'X'.

Technical drawing of a casting part (Figure 10.10) showing dimensions and details. The part is an L-shaped casting with a vertical leg and a horizontal leg. The vertical leg has a total height of 150, with a section of 85 and a section of 65. The horizontal leg has a total width of 85. The thickness of the vertical leg is 10, and the thickness of the horizontal leg is 10. The inner radius of the corner is 18.9. The distance from the bottom of the vertical leg to the start of the horizontal leg is 51.1. The drawing includes three detail views: DETAIL 1 (top left corner), DETAIL 2 (bottom left corner), and DETAIL 3 (bottom right corner). The casting side is indicated by a triangle and the text "stortzijde / côté coulage" and "Gussseite / casting side".


L 200
(300)
(400)

plank dikte 6cm
planche épaisseur 6cm
plank thickness 6cm


DETAIL 1




DETAIL 2




DETAIL 3



DETAIL 4



DETAIL 5



CLF10GS 150x100

sterkteklasse / classe de résistance Festigkeitsklasse / strength class	C60/75	artikelnr. / numéro d'article Article / item number	12000
constructieklasse / classe structurelle Bauklasse / structural class	S1	versie / version Version / version	20210607
betondekking / enrobage de béton Betondeckung / concrete cover	30mm	productie / production Herstellung / production	Wielsbeke
milieuklasse / classe d'exposition Expositionsklasse / exposure class (EN 206)	B / NL: XC4, XD3, XS3, XF4* F / UK: XC4, XD1, XS1, XF3* D: XC4, XF3*	volume / volume Volumen / volume	0.2282 m³
omgevingsklasse / classe d'environnement Umgebungsklasse / environmental class (NBN B15-001)	EE4/ES4*	gewicht / poids Gewicht / weight	555 kg
staalqualiteit / qualité de l'acier Stahlqualität / steel quality	B500B*	ankers / ancrés Anker / anchors	KKA: 1x 2.5T-55mm
toelaatbare maatafwijking / écart dimensionnel admissible zulässige Maßabweichung / allowable dimensional deviation	+5mm/-5mm	hijshaken / anneaux de levage Kupplungen / lifting links	1x HEFH KKA 2.5
stortzijde / côté coulage Gussseite / casting side	afgestreken / tiré à la règle abgestrichen / levelled		
betonafmetingen / dimensions de béton Betonabmessungen / concrete dimensions	cm		
andere afmetingen / autres dimensions andere Abmessungen / other dimensions	mm		

* andere klassen op aanvraag / autres classes sur demande / other classes on request / andere Klassen auf Antrag

